

INTERLINK TOWER

TECHNICAL SPECIFICATIONS

External Surfaces of the building:

Surfaces will be covered with marble, granite, fair face, alucobond, high quality textured graffiato and double glazing

OFFICES:

Reception Area:	Covered with granite, marble and wood
Reception Area of each floor:	Covered with granite, marble and wood
Layout of Area:	Office areas will be open plan with no partitions apart from the toilets and kitchen area
Flooring:	Raised floors of value €50/m ² including fittings
False Ceiling:	According to the detailed agreed plans valued at €17.10/ m ² .
Air-conditioning:	Type V.R.V. to meet the requirements of the office space.
Lighting:	18 points for every office area of 350 m ² .
Power Supply:	The initial cost of electricity load shall be paid by the company to the electricity board. For any additional load, you will be charged accordingly.
Glazing:	Double Glazing

Advertising Signs: Can be positioned in specific areas at the front of the building on the ground floor.

SHOPS:

Layout of Area: Office areas will be open plan with no partitions apart from the toilets and kitchen area

Flooring: Ceramic Tiles or high resistance granite of value €50/m²

False Ceiling: According to the detailed agreed plans valued at €17.10/ m².

Air-conditioning: Type V.R.V. to meet the requirements of the shop space.

Lighting: 1 point for every 25m²

Power Supply: The initial cost of electricity load shall be paid by the company to the electricity board. For any additional load, you will be charged accordingly.

Glazing: 16mm (8mm+8mm) laminated glass 5.10m high.

Advertising Signs: Can be positioned in specific areas at the front of the building on the ground floor.